



Key Features

- 4,000 ANSI Lumens offering bright images in any environment
- 1080p Full HD resolution for captivating visuals
- Unveil hidden details with a high native contrast ratio achieved through the 0.65" DMD chip
- Up to 300" screen size to maximize fun at home
- Easy multimedia access via dual HDMI ports and USB-A power supply



Product Description

The PX704HDE is a 4,000 ANSI Lumens lamp projector ideal for home and business use. Featuring a 1080p FHD resolution and up to 300" ultra-large projection, it showcases clear and vivid visuals for home entertainment and presentations. With a high native contrast ratio achieved through its 0.65" DMD chip, this projector showcases captivating visuals even with low-light movie scenes. It offers two HDMI ports for easy multimedia connectivity. Designed for enhanced functionality, it includes a USB-A output to power HDMI wireless dongles, eliminating the need for extra adapters. Whether tilted up or down, the auto V keystone feature ensures automatic image correction, keeping perfectly-aligned visuals. Maintenance is hassle-free – simply use a laptop and USB cable for software updates.





- 1. Adjustment Foot
- 2. Lens
- 3. Front IR
- 4. HDMI(HDMI 1.4/HDCP 1.4)
- 5. USB-A (5V/1.5A, Service)
- 6. RS232
- 7. Audio In

- 8. AC In
- 9. Kensington Lock
- 10. Audio Out
- 11. Focus Ring
- 12. Zoom Ring
- 13. LED Indicator
- 14. Keypad

Visit Us

www.viewsonic.com



SPECIFICATION

Native Resolution:	1920x1080
Brightness:	4000 (ANSI Lumens)
Contrast Ratio with SuperEco Mode:	25,000:1
Display Color:	1.07 Billion Colors
Light Source Type:	240W UHP Lamp
Light Source Life (hours) with Normal Mode:	4000
Light Source Life (hours) with SuperEco Mode:	15000
Lens:	F=2.5-2.67, f=21.8-24.0mm
Projection Offset:	132%+/-10%
Throw Ratio:	1.48-1.62
Optical Zoom:	1.1x
Digital Zoom:	0.8x-2.0x
Image Size:	30"-300"
Throw Distance:	1m-10m (100"@3.28m)
Keystone:	+/- 40° (V)
Audible Noise (Normal):	34dB
Audible Noise (Eco):	25dB
Input Lag:	16ms
Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Horizontal Frequency:	15K-102KHz
Vertical Scan Rate:	23-120Hz
INPUT	
HDMI:	2 (HDMI 1.4/ HDCP 1.4)
Audio-in (3.5mm):	1
OUTPUT	
Audio-out (3.5mm):	1
Speaker:	3W
USB Type A (Power):	1 (5V/1.5A)
CONTROL	
RS232 (DB 9-pin male):	1
USB Type A (Services):	1 (share with USB A Output)

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)
Power Consumption:	Normal: 295W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.70kg
Gross Weight:	3.80Kg
Dimensions (WxDxH) with Adjustment Foot:	309x234x115mm
Packing Dimensions:	400x337x168mm
OSD Language:	English, German, French, Swedish, Spanish, Portuguese, Polish, Dutch, T. Chinese, S.Chinese, Finnish, Korean, Russian, Hungarian, Czech, Arabic, Thai, Turkish, Vietnamese, Indonesian, Greek, Italian, Japanese, Total 23 languages
User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, Total 20 languages

STANDARD ACCESSORY

Power Cord:	1
Remote Control:	1
QSG:	Yes
Air Filter:	Yes (CN Only)
Warranty:	*Warranty offered may differ from market to market

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-129
Air Filter:	RSPL
Wall/Ceiling Mount:	PJ-WMK-007
Carry Bag:	PJ-CASE-008

