

ZH400UST

Laser 1080p Ultra Short Throw Projector



© Samruh Creative Association

- **Bright Full HD 1080p laser projector - 4000 ANSI lumens**
- **Ultra short throw lens - 100" image from less than half a metre away**
- **30,000 hours maintenance-free laser light source**
- **Dust resistant – Independently tested, IP5X certification for total reliability**

The ZH400UST is powered by long-lasting, low maintenance DuraCore laser light source. The lamp-less and filter-free design vastly reduces running costs for a low total cost of ownership.

Weighing only 5.6kg, this projector can be mounted just centimetres away from a wall or surface and can project an image size of over 100 inches (254cm).

Supporting 24/7 operation and versatile orientation, the ZH400UST is a flexible, powerful and bright ultra short throw projector which makes for a superb signage solution where space or accessibility can be limited, such as shop windows or retail displays.



Specifications

Display/image	
Display technology	DLP
Resolution	1080p Full HD (1920x1080)
Brightness	4,000 lumens
Contrast ratio	100,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-15°
Horizontal scan rate	15.3 ~ 91.1KHz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	2.21m ~ 2.59m (87" ~ 102") diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	0.25:1
Projection distance (m)	0.45m - 0.59m
Zoom type	Fixed
Focal length (mm)	3.72
Native offset	120%
Connectivity	
Connections	<p>Inputs 2 x HDMI 1.4a 3D support, 2 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm, 1 x Audio RCA L&R</p> <p>Outputs 1 x VGA shared with VGA2, 1 x Audio 3.5mm, 1 x USB-A power 2A</p> <p>Control 1 x RS232, 1 x RJ45, 1 x mini USB service, 1 x USB-A wireless</p>
General	
Noise level (typical)	30dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	18 languages: Arabic, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional), Turkish
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Yes
Heat dissipation	890BTU/hour
Speaker count	1
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200, WUSB
Networking	
LAN - control	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	210W
Power consumption (max)	330W
Weight and dimensions	
Net weight	5.6kg
Dimensions (W x D x H) mm	382 x 310 x 124

